



ADS800

Automatic Degreasing System

For degreasing parts to increase productivity



- CE compliant
- Contract life guarantee
- Water soluble biodegradable solution
- 140 litre capacity
- Water based cleaning solution not classified as toxic, corrosive, harmful or flammable
- Basket inching facility (for ease of load / unload)
- Automatic heated wash cycle
- High quality stainless steel
- Free of volatile organic compounds (VOC)
- Oil skimmer (optional extra)

NOTE: up to operating temperature >1 hour.
Average cleaning time: 10 minutes at 60°C.

SPECIFICATIONS

- Cleaning solution: contains corrosion inhibitors
- Cleaning solution volume: 140 litres
- Load capacity on tray: 250kg
- Typical wash cycle: 10 minutes at 60°C
- Electrical specification: 400V, 32A
- Equipment type: stainless steel
- Oil skimmer: optional extra

For use with ADS Power Clean / Storm1 / Super Bee LFG 300 solutions

ADS800


Automatic Degreasing System



Size perspective of basket



Top, Bottom and Side Spray Booms



Basket Stepping Facility



Quick Connection Component Exchange



Safety interlock mechanism



415 volt 32amp 3 phase Neutral & Earth power supply



Insulated locking handle



Control Panel

TECHNICAL SPECIFICATIONS

Voltage	380 - 415 V AC 50Hz
Current rating	32 Amp, 5 Pin, N & E
Protection Level	IP 54
Machine power	8.6 kW
Temperature (min/max)	50°C - 60°C
Wash cycle	1 – 60 min.
Spray pressure	3.6 - 5.5 Bar
Pump flow	150 litres per minute
Internal operating clearance (from basket to underside of lid)	600 mm
Maximum height (open lid)	1923 mm
Minimum height (closed lid)	1404 mm
Basket diameter	800 mm
Maximum loading capacity	250 kg
Volume of solution (minimum/optimum/maximum)	90/115/140 litres
Working solution level – min/max	90 - 140 litres
Overall machine dimensions L x W x H	955 x 1390 x 1405
Weight	220 kg
Optional	Oil skimmer